



Features

- For maintenance-free lead-acid batteries, 1 or 2 batteries
- 12V or 24V Batteries
- Protection for short-circuit with installed fuse
- Mountable with screws
- IP20
- Battery simply clamps into Aluminium base
- For battery sizes: 1.2Ah, 3.0Ah, 7.2Ah and 12Ah.



SPECIFICATIONS

BATTERY HOLDER	12V		24V (2 x 12V Batteries)			
Standard Version Code	BATTHOLDER 123	BATTHOLDER 127	BATTHOLDER 1.2	BATTHOLDER 3.2	BATTHOLDER 7.2	BATTHOLDER 12
DIN Rail Code	BATTHOLDER 123DIN	BATTHOLDER 127DIN	BATTHOLDER 1.2DIN	BATTHOLDER 3.2DIN	BATTHOLDER 7.2DIN	Not Available
Short-circuit protection	Yes – with fuse.					
Protection fuse	25A					
Ambient temperature (operation)	-25 to +50 °C (depends on battery)					
Ambient temperature (storage)	-20 to +50 °C					
Protection class	IP20					
Dimensions - mm (W x H x D)	105 x102 x 87.5	105 x 102 x 120.5	170 x 102 x 80	170 x 102 x 87.5	170 x 102 x 120.5	236 x 102 x 120.5
Weight (Standard)	0.19 kg	0.20 kg	0.28 kg	0.28 kg	0.29 kg	0.39 kg
Weight (DIN Rail)	0.21kg	0.22kg	0.30kg	0.30kg	0.31kg	n/a
Assembly (Std. version)	Mounting with M4 screws					
Assembly (DIN version)	Available only on BATTxxx DIN code					